


CIRCUIT DIAGRAM



Compliance: RohS II (2011/65/EU)

Tolerances: ±0.2mm	Date	Name
	07/09	dr
Travel	09/18	dr
Modifications	Date	Name

**TS 21 x**

**30 18 91**

Page

1/2

**knitter-switch**

Specifications:

Contact rating: 50mA, 12V DC  
 Contact resistance: 100mOhm max.  
 Insulation resistance: 100MOhm min.  
 Dielectric strength: 250V AC (50/60Hz) for 1 minute  
 Operating temperature: -25°C to +70°C  
 Storage temperature: -30°C to +80°C  
 Operating force: x, see table  
 Soldering conditions: pre-heat: max. 120°C, max. 360sec.  
 soldering: max. 265°C, max. 10sec.  
 Travel: 0.35 +/-0.1 mm  
 Material: Cover: stainless steel  
 Stem: high-temp. thermoplastic nylon UL94V-0  
 Contact: phosphor bronze, with silver cladding  
 Terminal: brass, with silver cladding  
 Base: high-temp. thermoplastic nylon UL94V-0, molded black

x	Operating force (gf)	Stem color	Life cycles
N	160 +/-50	brown	200 000
R	260 +/-50	red	100 000
S	320 +/-80	salmon	100 000
Y	520 +/-130	yellow	100 000

Compliance: RohS II (2011/65/EU)

Tolerances: ±0.2mm			Date	Name	<b>TS 21 x</b>
			07/09	dr	
			<b>knitter-switch</b>		<b>30 18 91</b>
Travel	09/18	dr			Page
Modifications	Date	Name			2/2