



Lxxx	LED
L6R	red, 6V AC/DC
L12R	red, 12V AC/DC
L24R	red, 24V AC/DC
LA1R	red, 110V AC
LA2R	red, 220V AC
L6B	blue, 6V AC/DC
L12B	blue, 12V AC/DC
L24B	blue, 24V AC/DC
LA1B	blue, 110V AC
LA2B	blue, 220V AC
L6W	white, 6V AC/DC
L12W	white, 12V AC/DC
L24W	white, 24V AC/DC
LA1W	white, 110V AC
LA2W	white, 220V AC
L6Y	yellow, 6V AC/DC
L12Y	yellow, 12V AC/DC
L24Y	yellow, 24V AC/DC
LA1Y	yellow, 110V AC
LA2Y	yellow, 220V AC
L6G	green, 6V AC/DC
L12G	green, 12V AC/DC
L24G	green, 24V AC/DC
LA1G	green, 110V AC
LA2G	green, 220V AC

Specifications:

Rated current / voltage: 12 mA / 10 mA; 6 V AC/DC
 18 mA / 16 mA; 12 V AC/DC
 10 mA; 24 V AC/DC
 2 mA; 110 V AC
 1 mA; 220 V AC

Vibration resistance: 10-55 Hz amplitude 0.5 mm

Operating temperature: -25°C to +55°C

Storage temperature: -40°C to +85°C

Compliance: RohS II (2011/65/EU)

Tolerances:			Date	Name	<h1>ICE Lxxx</h1> <h2>LED-Lamp</h2> <h3>30 41 14</h3>	Page 1/1
			07/18	dr		
Modifications			Date	Name	knitter-switch	