


**PANEL MOUNTING**



**CONTACT ARRANGEMENT**

code for x	function	toggle towards keyway	toggle opposite to keyway
N	On-On	1-2, 4-5	2-3, 5-6
R	Mom-On	1-2, 4-5	2-3, 5-6

code for x	function	toggle towards keyway	toggle in center	toggle opposite to keyway
P	On-Off-On	1-2, 4-5	open	2-3, 5-6
S	Mom-Off-Mom			
T	Mom-Off-On			
PA	On-On-On	1-2, 4-5	1-2, 5-6	2-3, 5-6
SA	Mom-On-Mom			
TA	Mom-On-On			

**Specifications:**

**Contact rating:** 3A, 250V AC / 6A, 125V AC  
 4A, 30V DC / 5A, 12V DC  
 6A, 6V DC

**Contact resistance:** 20mOhm max.

**Insulation resistance:** 1 000MOhm min. at 500V DC

**Dielectric strength:** 1 500V, 50Hz for the duration of 1 minute

**Operating temperature:** -45°C to +140°C

**Mechanical life:** min. 200 000 cycles (SA, TA: 100 000 cycles)

**Soldering conditions:** hand-soldering: max.: 420°C, 3sec., 60W  
 auto-soldering: max.: 270°C, 5sec.

**Mounting instruction:** max. torque: 49Ncm

**Material:** Terminal: brass, C1020 silver plated  
 Case: DAP  
 Housing: stainless steel, CNS9265  
 Bushing: copper alloy, C3604BD nickel plated  
 Actuator: copper alloy, C3604BD chrome plated

**Included accessories:** 1 pc. nut M6x0.75, nickel plated, 9mm wrench size  
 1 pc. tooth washer  
 1 pc. O-ring

**Sealing:** IP 67

**Compliance:** RohS III (2015/863/EU)

Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm	Date	Name	<b>MTE 206 x</b>
	11/09	dr	
Function table	10/19	dr	<b>30 19 57</b>
Dimension	01/11	dr	
Sealing	12/10	dr	
Modifications	Date	Name	<b>knitter-switch</b>
			Page 1/1